

Fair Profiles



PM-Profiles

Features

- for fast and easy assembly of e. g. exhibition stands etc.
- aluminium, anodized
- made according to DIN 17615
- light, solid, nice design
- enables angular connections
- with our fast-clamped connections very firm, stress, reversion and bending resistant profile connections are produced by means of profile bore holes and clamping pieces

Technical Data

	PM 50	PM 100
dimensions (W x H)	50 x 50 mm	100 x 100 mm
length	up to 3 m (special lengths upon request)	
weight	1,700 g/m	3,270 g/m
	8 T-groove indentions in an angle of 45° hollow indentation, Ø 8.5 mm for M10	8 T-groove indentions in an angle of 45° hollow indentation, Ø 8.5 mm for M10
inertia moment I_x	12.27 cm ⁴	107.20 cm ⁴
inertia moment I_y	12.27 cm ⁴	107.20 cm ⁴
moment of resistance W_x	4.91 cm ³	21.44 cm ³
moment of resistance W_y	4.91 cm ³	21.44 cm ³

Ordering Data

profile designation	Art. No: L = 1000 Art. No: L = 3000
PM 50 W 50 x H 50 mm	200 004 1000 200 004 3000
PM 100 W 100 x H 100 mm	200 005 1000 200 005 3000

Dimension Drawings

